Zeitschrift:	IABSE reports = Rapports AIPC = IVBH Berichte
Band:	64 (1991)
Artikel:	Foundations of bridge piers across the Volga and Buzan Rivers
Autor:	Dmitrievsky, B.P. / Kharebava, Zh.A.
DOI:	https://doi.org/10.5169/seals-49279

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. <u>Siehe Rechtliche Hinweise.</u>

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. <u>Voir Informations légales.</u>

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. <u>See Legal notice.</u>

Download PDF: 30.03.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch



Fondations des piles de ponts sur la Volga et la Bouzan

Gründung der Strompfeiler von Brücken über die Wolga und den Bouzan

B.P. DMITRIEVSKY

Civil Engineer Giprotransmost Moscow, USSR

Zh.A. KHAREBAVA

Civil Engineer Mostostroy 3 Saratov, USSR

In construction of foundations of bed piers under the complex engineering and geological conditions of the lower reaches of large rivers featuring considerable depths, low location of hard bedrock, weak drifts of substantial thickness, intensive navigation, etc., a demand arose in the elaboration of new structural and technological concepts whereby a sufficient operational reliability is combined with industrial method of work performance, lowering of material and labour ex penditure.



Fig. 1 Pier diagram.

For the first time in country's practice while erecting a city bridge across the Volga river in the town of Astrakhan and motor transport bridge across the Buzan river new solutions specified below (Fig.1) were run in. The two passages feature natural depths up to 28 m, flow rates up to 2.5 m/s, arrangement of the ground roofing facilitating reliable funding (of hard and semi-hard clays) at the depths up to 30 below bottom elevation.

The elaborated technology makes it possible to construct the drill columns of up to 2.0 m in diameter having the 3.5 m broadening at the bottom at depths up to 30 m below the bottom elevation.

Column pressing statical test with application of load up to 2000 kn were performed.

The pier foundations were built from islands having the sheet piling at depths up to 8-10 m, at larger depths selflifting platforms using travelling wharfs (MK-67 were employed.

The column construction started with immersion of the plan manufactured diameter 1720 or 2020 mm steel pipes until the clay roofing.

Upon removal of sand from the pipe cavities by a grab or airlift, the Japanese machines Kato-30TH or Kato-50TH were used for drilling dia. 1500 or 1700 mm wells to the design elevations. For making broadenings, use was made of the UHVIC universal reamers, or the reamers from the Kato-TH-50 mashine set. Reinforcing cages were lowered into the wells and by a method of the vertically moving pipe, filling of wells with concrete was achieved. All works were done at the not less than 4 m excessive pressure of water.

In concreting the grid foundations use was made of the suspended inventory lintels.

The applied technology is highly effective ensuring considerable reduction, as compared with other probable versions, of material expenditure, labour input and construction costs, which determined its wide application in designing and construction of bridges under similar conditions.