

**Zeitschrift:** IABSE congress report = Rapport du congrès AIPC = IVBH  
Kongressbericht

**Band:** 12 (1984)

**Artikel:** Distribution of wheel loads on highway bridges

**Autor:** Sanders, Wallace W.

**DOI:** <https://doi.org/10.5169/seals-12236>

### Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Siehe Rechtliche Hinweise.

### Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. Voir Informations légales.

### Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. See Legal notice.

**Download PDF:** 25.04.2025

**ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>**



## Distribution of Wheel Loads on Highway Bridges

**Wallace W. SANDERS, Jr.**

Prof. Dr.

Iowa State University

Ames, IA, USA

The current criteria for the distribution of wheel loads in the U.S. bridge specifications have been undergoing change and expansion for over 50 years. The changes have primarily been introduced as modifications for a specific bridge type or condition with variations in the factors considered. As a result, the approach to the criteria has varied and resulted in inconsistencies in the codes. There now is a need for a complete review of load distribution in bridges recognizing a consistent approach to all bridge types and the availability of high speed computation.

There are a number of methods of analysis that can be used to develop load distribution behavior. These methods include: orthotropic plate, finite element or strip, grillage analogy, folded plate, influence surfaces. Using the selected methods, the effects of aspect ratio, bridge stiffness parameter, edge effects, load position, skew, continuity and diaphragms need to be evaluated for the broad types of bridges.

This study is needed and should result in a consistent criteria format based on similar parameters. It should consider all factors which affect behavior. The option should be available and encouraged to use one of the theories for complex structures, while providing a simple format for simple bridges.

# DISTRIBUTION OF WHEEL LOADS ON HIGHWAY BRIDGES

## Abstract



The current criteria for the distribution of wheel loads in the U.S. bridge specifications have been undergoing change and expansion for over 50 years. The changes have been primarily introduced as modifications for a specific bridge type or have been made with variations in the factors considered. As a result, the approach to the problem has varied and resulted in inconsistencies in the codes. There now is a need for a complete review of load distribution in bridges recognizing a common approach to all bridge types and the availability of high speed computation.



## Method of Analysis

1. Orthotropic plate
2. Finite element or strip
3. Grillage analogy
4. Folded plate
5. Influence surfaces

## Design Criteria

STANDARD SPECIFICATIONS FOR HIGHWAY BRIDGES														
 The American Association of State Highway and Transportation Officials DIVISION I - DESIGN 1983 EDITION C91														
 H20-44 8,000 lbs 12,000 lbs 32,000 lbs  14,000 lbs	<b>Percentage of Live Loads:</b> One or two lanes 100% Three lanes 90% Four lanes or more 75%	<b>Traffic Lanes:</b> 12 ft. wide lanes (with 10 ft. wide truck), spaced across the entire bridge roadway width. Lanes shall be placed in numbers and position to maximize effect.												
<b>Interior Beams: Wheel Load Fraction (typical)</b> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Kind of Floor</th> <th>Bridge Designed for One Traffic Lane</th> <th>Bridge Designed for Two or More Traffic Lanes</th> </tr> </thead> <tbody> <tr> <td>Timber: E-Glued Laminated Panels on Glued Lam. Stringers</td> <td>5.6.0</td> <td>5.5.0</td> </tr> <tr> <td>Concrete: Steel I-Beam Stringers or P.C. Girders</td> <td>5.7.0</td> <td>5.5.5</td> </tr> <tr> <td>Concrete Box Girders</td> <td>5.8.0</td> <td>5.7.0</td> </tr> </tbody> </table>	Kind of Floor	Bridge Designed for One Traffic Lane	Bridge Designed for Two or More Traffic Lanes	Timber: E-Glued Laminated Panels on Glued Lam. Stringers	5.6.0	5.5.0	Concrete: Steel I-Beam Stringers or P.C. Girders	5.7.0	5.5.5	Concrete Box Girders	5.8.0	5.7.0	<b>Exterior Beams:</b> a. Edge beam position; or b. Load fraction = $S/4L + 25\%$ ( - 4 steel stringers; S = E - 14 )	<b>Special:</b> Spread Box Girders: Interior Load Fraction $\frac{2N_1 - N_2}{N_1}$ Composite Box Girders: Load Fraction $0.1 - 1.7R \frac{N_1}{N_2}$
Kind of Floor	Bridge Designed for One Traffic Lane	Bridge Designed for Two or More Traffic Lanes												
Timber: E-Glued Laminated Panels on Glued Lam. Stringers	5.6.0	5.5.0												
Concrete: Steel I-Beam Stringers or P.C. Girders	5.7.0	5.5.5												
Concrete Box Girders	5.8.0	5.7.0												

## Factors Affecting Design

1. Aspect ratio
2. Bridge stiffness parameter
3. Edge effects
4. Load position
5. Skew
6. Continuity
7. Diaphragms (type, location)

## Specification Problems

1. Criteria format not consistent
2. Basis for criteria varies
3. Critical factors not considered
4. New bridge types require special studies
5. Loading conditions changed
6. Inconsistent safety factors
7. No criteria for rating

## Current Design Practice

1. Timber deck/timber stringers
2. Concrete deck steel I-beams
3. Concrete deck P.C. girders
4. Steel grid decks/any stringer
5. Concrete deck concrete T-beams
6. Segmental box girders
7. Concrete deck/spread box beams

## Future Criteria

1. Load distribution criteria centralized
2. Simple criteria for "simple" bridges; Complex theories for "complex" bridges encouraged
3. Adaptable to all types of bridges
4. Separate design and rating criteria
5. Complete criteria for moment and shear