

English translation of part of the text of pages 13, 14 and 15 of the book: **Beulwerte ausgesteifter Rechteckplatten, von K. Klöppel und K.H. Möller**

Autor(en): [s.n.]

Objektyp: **Article**

Zeitschrift: **IABSE reports of the working commissions = Rapports des commissions de travail AIPC = IVBH Berichte der Arbeitskommissionen**

Band (Jahr): **11 (1971)**

PDF erstellt am: **14.08.2024**

Persistenter Link: <https://doi.org/10.5169/seals-12080>

Nutzungsbedingungen

Die ETH-Bibliothek ist Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Inhalten der Zeitschriften. Die Rechte liegen in der Regel bei den Herausgebern.

Die auf der Plattform e-periodica veröffentlichten Dokumente stehen für nicht-kommerzielle Zwecke in Lehre und Forschung sowie für die private Nutzung frei zur Verfügung. Einzelne Dateien oder Ausdrucke aus diesem Angebot können zusammen mit diesen Nutzungsbedingungen und den korrekten Herkunftsbezeichnungen weitergegeben werden.

Das Veröffentlichen von Bildern in Print- und Online-Publikationen ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Die systematische Speicherung von Teilen des elektronischen Angebots auf anderen Servern bedarf ebenfalls des schriftlichen Einverständnisses der Rechteinhaber.

Haftungsausschluss

Alle Angaben erfolgen ohne Gewähr für Vollständigkeit oder Richtigkeit. Es wird keine Haftung übernommen für Schäden durch die Verwendung von Informationen aus diesem Online-Angebot oder durch das Fehlen von Informationen. Dies gilt auch für Inhalte Dritter, die über dieses Angebot zugänglich sind.

**English Translation of part of the text of pages 13, 14 and 15 of the book:
Beulwerte ausgesteifter Rechteckplatten, Vol. II by K. Klöppel and
K.H. Möller, Editor W. Ernst und Sohn, Berlin, 1968
(Reproduced with the Permission of Professor K. Klöppel)**

Traduction anglaise d'une part du texte des pages 13, 14 et 15 du livre:
Beulwerte ausgesteifter Rechteckplatten, Vol. II par K. Klöppel et
K.H. Möller, Editeur W. Ernst und Sohn, Berlin 1968
(reproduit avec l'autorisation du Prof. K. Klöppel)


Englische Übersetzung eines Teils des Textes der Seiten 13, 14 und 15 des
Buches:
Beulwerte ausgesteifter Rechteckplatten, Bd. II von K. Klöppel und
K.H. Möller, Verlag W. Ernst und Sohn, Berlin 1968
(Mit Genehmigung von Prof. K. Klöppel)

Page 13.

In the use of tables for uniformly distributed stiffening, it is necessary exert caution about two questions :
First, about the calculations of the effective moment of inertia, secondly, about the safety required against buckling.
The Standard DIN 4114 Ri 18.13. accepts, for eccentric stiffeners, to relate the moment of inertia to the upper edge of the plate. The basis of this rule is an assumption about the effective width of a corresponding strip of the buckled plate. But when the stiffeners are regularly spaced, the effective width cannot be larger than the distance between two stiffeners.

If the moment of inertia of such a plate strip is calculated, then values significantly smaller than according to DIN 4114 are usually obtained. For closely spaced stiffeners, it is therefore always recommended to calculate the moment of inertia both according to the Standard and also for a plate strip composed of a stiffener and a web strip having as width the distance between two stiffeners, the example figure 11 should serve an illustration. According to DIN 4114, the moment of inertia with respect to the upper edge of the web is

$$J_{DIN} = J_L + F_L (a - e_x)^2 = 611 + 23,2 \times (16 - 5,63)^2 = 3115 \text{ cm}^4$$



With the largest value for the effective width, namely the distance between two stiffeners, the distance of the centroid to the upper edge of the web is found to be, according to fig. 11 :

$$d_x = \frac{F_L \left(a + \frac{t}{2} - e_x \right)}{F_L + F_{web}} = \frac{23,2 (16 + 0,5 - 5,63)}{23,2 + 41} = 3,92$$

which yields

$$J = J_2 = F_L \left(a + \frac{t}{2} - e_x - d_x \right)^2 + F_{web} d^2 = 2360 \text{ cm}^4$$

It is seen therefore that J_{DIN} does not apply for the calculation of the buckling stress.

Page 14.

As already mentioned in the Introduction, one has to distinguish between the linear buckling, connected with idealized structural and geometrical assumptions, with the buckling load as limit load, which is the basis for the specification DIN 4114 and for the present book, and a second postcritical non linear buckling, described by non linear differential equations to which is associated a limit load which is called ultimate load. This load is regularly higher than the buckling load, because additional membrane stresses come into play. On this theoretically more complicated way, the influences of unavoidable initial deflections may also, for example, be taken in consideration. The ultimate load above the buckling load can be determined either by the entry into the plastic range or by inacceptably large deformations.

Page 15.

It is necessary to come back to the question whether by plate buckling a second equilibrium state establishes itself or not. Let us imagine the plate to be studied by linear buckling theory in the buckled state. In addition to the membrane stresses existing already before buckling, we have now flexural stresses, that may be considered to be produced by the fictitious transverse load

$$q = \sigma_x t \frac{\sigma_w^2}{\sigma_x^2} + \sigma_y t \frac{\sigma_w^2}{\sigma_y^2} + \tau t \frac{\sigma_w^2}{\sigma_x \sigma_y}$$

where σ_x , σ_y and τ are the edge stresses of the plate. If the buckling shape is not known, one shall imagine that the plate is subjected to a uniform transverse load. A large limit load is then to await, when these fictitious transverse loads are supported in all directions nearly on the same way, in other words when we have an extended plate action. If, on the contrary, these imagined transverse loads are supported only in the direction of the greatest compressive stresses, then we can as a good approximation to reality imagine the plate to be cut in strips by cuts parallel to the largest compressive stresses. The individual beamlike strip wall then behave like a buckled stult.

It is recommended now, for plates which support the fictitious transverse loads nearly uniquely in the direction of the large compressive stresses, to require larger safeties than $\varphi_b = 1,25$ or $\varphi_b = 1,35$.

According to the opinion of the authors, which is supported by sections 17.5 and 17.6 of the DIN 4114, safeties are to be required which in the limit case coincide with those for the compressed bar. Numerical comparisons have led to following formulæ - which cannot be demonstrated, which should give the required safety

$$\varphi_{Rk} = \frac{\varphi_k + 100 \bar{\alpha}^2 \varphi_B}{1 + 100 \bar{\alpha}^{-2}}$$

The side ratio $\bar{\alpha}$ is obtained through the differential equation of the orthotropic plate, under the assumption of a definite torsional rigidity, by a coordinate transformation. $\bar{\alpha}$ is the side ratio of an unstiffened comparison plate with the same buckling shape as the stiffened plate :

$$\bar{\alpha} = \alpha \sqrt[4]{\frac{1 + \Sigma \varphi_Q}{1 + \Sigma \varphi_2}}$$

An unstiffened plate with the side ratio α behave therefore similarly as an unstiffened plate with the side ratio $\bar{\alpha}$.

For the above example, (fig.11), $\varphi_L = 615$ and

$$\bar{\alpha} = 0,48 \sqrt[4]{\frac{1}{616}} = 0,096$$

According to Table 7 of DIN 4114, we have for loading case 1

$$\varphi_k = 2,18$$

and one obtains

$$\varphi_{Rk} = \frac{\varphi_k + 100 \bar{\alpha}^2 \varphi_B}{1 + 100 \bar{\alpha}^{-2}} = 1,69$$

This safety against buckling at least should be required, in this example, in the opinion of the Authors.

In the choice of the stiffener section, it must be in addition taken care that stiffeners do not buckle before reaching the plate buckling load.

Leere Seite
Blank page
Page vide