

# Prestressed concrete bridge with tendons of large eccentricities

Autor(en): **Yamazaki, Jun / Ido, Kosei / Kono, Hiroki**

Objektyp: **Article**

Zeitschrift: **IABSE reports = Rapports AIPC = IVBH Berichte**

Band (Jahr): **79 (1998)**

PDF erstellt am: **12.07.2024**

Persistenter Link: <https://doi.org/10.5169/seals-59857>

## **Nutzungsbedingungen**

Die ETH-Bibliothek ist Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Inhalten der Zeitschriften. Die Rechte liegen in der Regel bei den Herausgebern.

Die auf der Plattform e-periodica veröffentlichten Dokumente stehen für nicht-kommerzielle Zwecke in Lehre und Forschung sowie für die private Nutzung frei zur Verfügung. Einzelne Dateien oder Ausdrucke aus diesem Angebot können zusammen mit diesen Nutzungsbedingungen und den korrekten Herkunftsbezeichnungen weitergegeben werden.

Das Veröffentlichen von Bildern in Print- und Online-Publikationen ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Die systematische Speicherung von Teilen des elektronischen Angebots auf anderen Servern bedarf ebenfalls des schriftlichen Einverständnisses der Rechteinhaber.

## **Haftungsausschluss**

Alle Angaben erfolgen ohne Gewähr für Vollständigkeit oder Richtigkeit. Es wird keine Haftung übernommen für Schäden durch die Verwendung von Informationen aus diesem Online-Angebot oder durch das Fehlen von Informationen. Dies gilt auch für Inhalte Dritter, die über dieses Angebot zugänglich sind.

# Prestressed Concrete Bridge with Tendons of Large Eccentricities

**Jun YAMAZAKI**

Professor  
Nihon Univ.  
Tokyo, Japan

Born in 1942, received his degrees at Univ. of Tokyo and Univ. of Washington.

**Kosei IDO**

Graduate Student  
Nihon Univ.  
Tokyo, Japan

Born in 1973, graduate from Nihon Univ., College of Science and Technology.

**Hiroki KONO**

Graduate Student  
Nihon Univ.  
Tokyo, Japan

Born in 1973, graduate from Nihon Univ., College of Science and Technology.

## Summary

A model favorable in structural behavior and ease of construction was created based on a design rationale selected for prestressed concrete (PC) girder bridge with external tendon of large eccentricity. For a self anchored suspension PC bridge, possible minimum values were derived for girder depth, area, section modulus, tendon sag and prestressing force. For this type of structure a span length of about 180 m was found to be favorable. A finite deflection analysis suggested that ultimate state of 1.7 times (Dead load+ Live load) is not attained for span lengths larger than 180 m. Load test results for reduced scale specimen were satisfactory for preliminary plans and tests are being continued.




Fig.1 Prestressed concrete (PC) bridges with tendons of large eccentricity

## 1. Proportioning the structure for service load

A model chosen was mono-cable self-anchored PC suspension bridge (Fig.1,b). For an assumed live load of  $4 \text{ kN/m}^2$ , requirements set for proportioning were; (1) deflection due to live load is  $1/1000$  of span, (2) maximum fiber stress in concrete beam under extreme moments is  $10 \text{ MPa}$ , (3) ultimate tendon strength is  $1900 \text{ MPa}$ . In a simplified response model the assumptions were; (1) cable profile shape is parabola and remains as parabola after deflection, (2) cable and beam deflection is same at span center only and compatibility is ignored elsewhere, (3) and thus the beam is loaded downward by uniform design load and upward by uniform load from cable.




Fig.4 Cable sag




Fig.2 Structure profile shapes derived by stated rationale for varying span lengths




Fig.3 Cross section shapes




Fig.5 Girder depth



**2. Structural characteristic obtained**

In view of results shown in Figs.2 through 7, a proportion for a span length of 180m is found to be favorable in terms of response to service load and construction method. A stress increase due to live load in tendon was 7% of initial tension (Fig.6). Tendon is composed of 335 of 15.2mm strands and initial tension is 51,100kN (0.6 times the ultimate). A girder depth of 2.765m (Fig.3) and a height of deviator tower of 21.6m (Fig.2, span-sag ratio is 8.32) are favorable for current state of practice of construction method.




Fig.6 Stress increase in cable due to live load




Fig.7 Load shared by girder and cable

**3. Finite deflection analysis for ultimate**

An assumption of load sharing between cable and beam is same as stated before in Section 1. An analysis model is as shown in Fig.8. Load carrying capacity of the beam is reduced by axial force component of prestress as deflection increases. However, ultimate strength of 1.7 times (D+L) is attained for span length of 180m as seen in Fig.9.




Fig.8 Mechanics model for deflection analysis

**4. Load testing model**

Similitude of 1/24 scale model (Fig.10) was true for sag-span ratio and girder depth, but it was violated for girder cross section area and section modulus

(by factors not exceeding 2) and prestress. For elastic range of tendon, response to load was satisfactory to prediction including deflection (Fig.11) for preliminary stage of test plan.




Fig.9 Load vs deflection by finite deflection analysis




Fig.10 Scheme of load test apparatus (scale 1: 24)




Fig.11 Load vs deflection