

High performance concrete in the Argentinean West Central Area

Autor(en): **Morandi, Javier O. / Rio, Olga / Uliarte, Ricardo José**

Objekttyp: **Article**

Zeitschrift: **IABSE reports = Rapports AIPC = IVBH Berichte**

Band (Jahr): **83 (1999)**

PDF erstellt am: **17.09.2024**

Persistenter Link: <https://doi.org/10.5169/seals-62834>

Nutzungsbedingungen

Die ETH-Bibliothek ist Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Inhalten der Zeitschriften. Die Rechte liegen in der Regel bei den Herausgebern.

Die auf der Plattform e-periodica veröffentlichten Dokumente stehen für nicht-kommerzielle Zwecke in Lehre und Forschung sowie für die private Nutzung frei zur Verfügung. Einzelne Dateien oder Ausdrucke aus diesem Angebot können zusammen mit diesen Nutzungsbedingungen und den korrekten Herkunftsbezeichnungen weitergegeben werden.

Das Veröffentlichen von Bildern in Print- und Online-Publikationen ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Die systematische Speicherung von Teilen des elektronischen Angebots auf anderen Servern bedarf ebenfalls des schriftlichen Einverständnisses der Rechteinhaber.

Haftungsausschluss

Alle Angaben erfolgen ohne Gewähr für Vollständigkeit oder Richtigkeit. Es wird keine Haftung übernommen für Schäden durch die Verwendung von Informationen aus diesem Online-Angebot oder durch das Fehlen von Informationen. Dies gilt auch für Inhalte Dritter, die über dieses Angebot zugänglich sind.



High Performance Concrete in the Argentinean West Central Area

Javier O. MORANDI

Professor
Mat. and Soils Inst. – UNSJ
San Juan, Argentina

Javier Morandi, received his Civil Eng. Degree from the Univ. of San Juan. He obtained a Master in Construction in Spain. He has been working as professor in the UNSJ.

Olga RIO

Doctor in Civil Engineering
Eduardo Torroja Institute
Madrid, Spain

Olga Río, received her Civ. Eng. Degree from the Univ. of Tucumán; and her Doctorate degree at Univ. of Madrid. She has been working at the E. Torroja Inst. for the past 16 years.

Ricardo José ULIARTE

Professor
Mat. and Soils Inst. – UNSJ
San Juan, Argentina

Ricardo Uliarte, received his Civil Eng. Degree from the Univ. of San Juan. He obtained a Master in Structures in Chile. He has been working as lecturer in the UNSJ.

Keywords: HPC, additives, natural pozzolan, pozzolanic activity, mechanical properties.

Abstract

Active mineral additions, as components of concrete, make possible the enhancement of the mechanical resistance of the concrete. Besides, it allows preparing concrete with better durability properties, i.e. resistance against aggressive agents and lower development of hydration heat. Anyway, it is possible to get significant energy savings and design purpose made mixtures for specific structures located in special areas. This preparation of mixtures is what we call in this work HPC.

A lot of research works exist in relation to the use of active mineral additives (micro-silex, fly ashes, metha-kaolin, etc.) in the elaboration of HPC. Physic-chemistry properties of these additions are variable and the action mechanism is controlled by the pozzolan reaction. The mechanical properties of the HPC, also depend on the characteristic of the granular materials used. There are considerable differences on the mechanical behaviour of HPC, inclusive with the same resistance, depending on these variables and on where they are been manufactured^[1]. The characterisation of natural pozzolan of volcanic origin and diatomaceous ground extracted from local quarries, of the area of the Andes mountain range (San Juan and Mendoza provinces) in the region of "Cuyo", (the region of Cuyo is located in the Argentinian West Central area) with the purpose of being employed, as active mineral additives, is shown in this work. Preliminary geologic surveys, specimen collection and tests for physical chemical characterisation were also carried out.

The most interesting samples were selected to investigate the effect of fineness and granulometry on the pozzolanic activity. In addition, some concrete samples were made to evaluate traction and compression mechanical properties and their evolution in time. All the results of these samples are also presented. The work presented in this paper is part of a greater research project which aim is the evaluation of the technical and economical possibilities for using this HPC, made with local materials, in building structures of the Argentinian West Central area. This area is, on the other hand, the zone of maximum seismic risk in this country.



Nevertheless, it is necessary to investigate further in the optimisation and study of structural elements under different load patterns, in order to use this HPC in the Cuyo region. As we mention before this is a high seismic region. The following conclusions of the first results can be pointed out:

- The pozzolanic activity of the samples studied has been tested and proved.
- The addition of active raw materials from the geographic area can be considered to be apt to elaborate concrete of especial properties. For instance, durability, i.e. sulphate attack resistance, and to control the hydration heat dissipation.
- Despite of having a lower efficiency than concrete prepared with microsilex, still it is possible to use the Pozzolan to make HPC.
- The cost of the quarry is around \$2 per ton. From the economic point of view is very interesting and can be considered to be apt.
- The fresh concrete has a slightly higher viscosity compared with the ones without pozzolan, but nevertheless is apt to be placed through difficult access places.
- Hardened shows increasing resistance up to one year, with a higher increase in the beginning due to the type of cement used.

Aknowlegments

The authors want to thanks, the other people of the Department of Structures and Soils of the University of San Juan, involve in the project, for their collaboration. Thanks also to Dr. Javier Turrillas and Soledad Alvarez for their technical and linguistic advice.

References

- [1] L. Coppola, "Design of Reiforced High Strength Concrete Structures", Mario Collepari Symposium on Advances in Concrete Science and Technology. P. K. Metha Ed. 1997.
- [2] Hanna, E; Luke, K; Perraton, D and Aitcin, P. C.; "Rheological Behaviour of Portland Cement Pastes in the Presence of a Superplasticizer", ACI SP 119. 1989.
- [3] Metha, P. K.; Aitcin, P. C.; "Microstructural Basis of Selection of Materials and Mix Proportions for High Strength Concrete". Second International Symposium on "Utilisation of HSC". May 1990. Berkeley. California.
- [4] Uliarte, R. J., Morandi J., "Utilización de hormigones especiales y dispositivos de disipación de energía en estructuras ubicadas en zona de alto riesgo sísmico". Primer Congreso Internacional de Tecnología del Hormigón. Buenos Aires - Argentina, Junio de 1998.