

# Dynamical load factor for highway bridge decks with pavement irregularities

Autor(en): **Santos da Silva, José Guilherme**

Objektyp: **Article**

Zeitschrift: **IABSE reports = Rapports AIPC = IVBH Berichte**

Band (Jahr): **83 (1999)**

PDF erstellt am: **15.08.2024**

Persistenter Link: <https://doi.org/10.5169/seals-62887>

## **Nutzungsbedingungen**

Die ETH-Bibliothek ist Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Inhalten der Zeitschriften. Die Rechte liegen in der Regel bei den Herausgebern.

Die auf der Plattform e-periodica veröffentlichten Dokumente stehen für nicht-kommerzielle Zwecke in Lehre und Forschung sowie für die private Nutzung frei zur Verfügung. Einzelne Dateien oder Ausdrucke aus diesem Angebot können zusammen mit diesen Nutzungsbedingungen und den korrekten Herkunftsbezeichnungen weitergegeben werden.

Das Veröffentlichen von Bildern in Print- und Online-Publikationen ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Die systematische Speicherung von Teilen des elektronischen Angebots auf anderen Servern bedarf ebenfalls des schriftlichen Einverständnisses der Rechteinhaber.

## **Haftungsausschluss**

Alle Angaben erfolgen ohne Gewähr für Vollständigkeit oder Richtigkeit. Es wird keine Haftung übernommen für Schäden durch die Verwendung von Informationen aus diesem Online-Angebot oder durch das Fehlen von Informationen. Dies gilt auch für Inhalte Dritter, die über dieses Angebot zugänglich sind.



## Dynamical Load Factor for Highway Bridge Decks with Pavement Irregularities

**José Guilherme SANTOS DA SILVA**  
Visitor Professor  
UERJ/FEN/MECAN  
Rio de Janeiro, Brazil

José Guilherme Santos da Silva, born 1965, received his D.Sc. degree in civil engineering-structures from PUC-Rio. His research interests include structural dynamics and solid mechanics.

### Summary

Since long time the dynamical actions of moving vehicles on bridge decks have been present in structural engineering concerns. In the last few decades the scientific community has started a continuous effort on the study of the dynamical effects on bridge superstructures due to the vehicle traffic on irregular pavement surfaces. In design practice, most of the technical recommendations use a dynamical load factor applied to the vehicle static effects to take into account all the dynamical actions. One presents now the results of a study to verify the extension of the dynamical effects, displacement and stresses, on highway bridge decks, due to vehicles crossing on the rough pavement surface defined by a probabilistic model.

**Keywords:** bridge structural dynamics, highway bridges, bridge pavement roughness.

### Abstract

Since the late 80's, many efforts have been taken to study the dynamical effects on highway bridge decks due to the interaction of the vehicle suspension flexibility with the irregular pavement surface. Several studies have made evident that such effects are much more important than those for a smooth vehicle movement on the bridge [1,2,3,4].

In design practice, the displacements and stresses of the dynamic actions are taken in account, in general, by means of a dynamical load factor (DLF) applied to the static effects of the moving vehicles. In most of the countries, including in Brazil, the code recommendations propose formulas to evaluate the DLF based only on the bridge span length.

In addition to these points, field reports say that some bridges have been submitted to excitation levels, under usual traffic conditions, which have deteriorated their service conditions and structure durability; this can be an indication of under conservative DLF. So, it is desirable to have the problem parameters quantitatively evaluated to better estimate their participation in the structure disruption and to review quantitatively the definition of the DLF for lower quality pavement surfaces.

This ensemble of papers that have been published since then made evident that the dynamic effects produced by the oscillation of the vehicle vs. rough pavement interaction force is a main factor in establishing the DLF value [4,5,6,7,8,9].

In this work one considers a probabilistic definition for the pavement irregular profile and a mathematical structural model which includes the interaction between the dynamical properties of the vehicle with those of the bridge. The moving load is formed by an infinite train of similar

vehicles regularly spaced and running at constant speed, in such way to obtain steady-state mean maximum response quantities of the bridge deck, which are necessary to a fatigue analysis of the deck material; one also considers the generation of a number of pavement surface profiles sufficiently large to sustain a statistical treatment of the results [4,5,8,9].

This analysis methodology is applied to reinforced concrete beam decks, continuous on several supports, with overhangs and with constant box cross section and one observes the node displacements and member stresses where the maxima occurs. A parametric study is developed and one concludes proposing a review on the evaluation of the DLF and on qualitative and quantitative aspects of the problem and the attitudes concerned with bridge design and maintenance.

The main point in this work is the magnitude of dynamical effects relatively to the static values. The roughness of an excellent pavement surface produces response quantities, displacements and stresses to as the bridge deck, that can reach magnitudes to the same order of those due to the static effect of a train of vehicles long enough to load all the bridge. These magnitudes are many times greater than that due to the load mobility alone [10].

## References

- [1] Ramalho, F. N. M. and Roehl, J. L., “Ações Dinâmicas em Pontes Rodoviárias com Defeitos na Pista”, X CILAMCE, Iberian Latin-American Conference on Computational Methods in Engineering, 1989.
- [2] Sedlacek, G. and Drosner, St., “Dynamik bei Brücken”, Baustatik Baupraxis, Universität. Hannover, 1990.
- [3] Wang, T. L. and Huang, D., “Cable-Stayed Bridge Vibrations due to Road Surface Roughness”, *ASCE, J. Struc. Engr.*, Vol. 118, n.º 5, pp.1354-1374, 1992.
- [4] Silva, J.G.S., “Análise Dinâmica Não-Determinística de Tabuleiros de Pontes Rodoviárias com Irregularidades Superficiais”, D.Sc. Thesis, Departamento de Engenharia Civil, PUC-Rio, 1996.
- [5] Silva, J.G.S. and Roehl, J.L., “Dynamical Analysis of Bridge Decks with Irregular Pavement Surface Defined by a Profile Spectral Density”, XVII CILAMCE, Iberian Latin-American Conference on Computational Methods in Engineering, 1996.
- [6] Silva, J.G.S.; Roehl, J.L., “Probabilistic Formulation for the Analysis of Bridge Decks with Irregular Pavement Surface”, VII DINAME, International Conference on Dynamic Problems in Mechanics, 1997.
- [7] Calçada, R.; Cunha, A., “Stochastic Modeling of the Dynamic Behavior of Bridges under Traffic Loads”, IV WCCM, Fourth World Congress on Computational Mechanics, 1998.
- [8] Silva, J.G.S.; Roehl, J.L., “Ações Dinâmicas em Tabuleiros de Pontes Rodoviárias Provenientes das Irregularidades do Pavimento”, III SIMMEC, 3<sup>o</sup> Simpósio Mineiro de Mecânica Computacional, In portuguese, 1998.
- [9] Silva, J.G.S.; Roehl, J.L., “Parametric Study of Highway Bridge Decks with Irregular Pavement Surface”, PACAM VI, VI Pan American Congress of Applied Mechanics and VIII DINAME, International Conference on Dynamic Problems in Mechanics, 1999.
- [10] Silva, J.G.S.; Roehl, J.L., “Dynamical Actions on Bridge Decks due to a Train of Vehicles”, IV WCCM, Fourth World Congress on Computational Mechanics, 1998.